

WONDER.D



The most Powerful LED Wash Light with the Hotspot Control



DOUBLE ZOOM
HOTSPOT CONTROL
FOUR INDEPENDENT LED SECTORS
PERFECT RGBW COLOR MIXING
LINEAR ZOOM 3.5° - 52°
ADJUSTABLE COLOR TEMPERATURE 2700 - 8000 K
SILENT OPERATION
'FPR' - FREE PAN ROTATION SYSTEM (DTS PATENT)
22,000 LUX @ 5 M
LIGHTWEIGHT: ONLY 22 KG

WONDER.D is the most powerful WASH LED projector. Its exclusive double concentric optical system with different linear zoom ranges, provides an adjustable hotspot useful to get an unprecedented evenly diffused wash effect; or a tight central beam and a wash projection all around. Moreover, as WONDER.D offers four independent LED sectors, it's like having four LED fixtures in one. WONDER.D is perfect in a range of applications, from live concert to congress halls. WONDER.D is equipped with 49 high power OSTAR RGBW LED delivering 24,500 Lumens.

WONDER.D



LED TECHNOLOGY

49 FULL COLOR LEDs (RGBW)

OPTICAL GROUP

2 concentric independent high efficiency optical groups

Optical group 1 (7 lenses): 3.5° - 52° long excursion linear motorized zoom
Optical group 2 (42 lenses): 8° - 52° long excursion linear motorized zoom
22,000 Lux / 5 m

COLOR GENERATION

4 discrete LED areas; each area is independently controllable

(luminosity, colors, effects)

16 million colors each
Wide palette of pure uniform whites with variable
linear color temperature (2700 K - 8000 K)

INTERFACE / CONTROL PROGRAMMING

LCD graphic display + 4 soft-keys (control / management of the main parameters)
RDM
Updatable internal operating system
Li-Fe display backup battery

DMX

34 DMX channels

PAN & TILT

'FPR' system (DTS patent)
Pan: limitless rotation, in both directions;
360° rotation in 1.56 sec.;
Tilt 270°: 1.5 sec.
Tri-phase stepper motor
Technology for ultra-fast silent movements
16-bit resolution
Selectable speed ranges
Pan / Tilt lock

POWER SUPPLY

Electronic full-range
AC 90-260 V 50/60 Hz
Power consumption: 850 W

CONNECTORS

DMX: 4 XLR connectors (3-pole In and Out; 5-pole In and Out) by Neutrik
Power supply: PowerCon In/Out (re-launch) connectors by Neutrik

OPERATING AMBIENT TEMPERATURE

-10° / 40°

PHYSICAL

Weight: 22 Kg
Dimensions: base 355x398 mm
Overall 512x398x525/590 h mm




INTERNATIONAL CERTIFICATIONS

Certification CE;
LED Class: Class 2 LED product


INCLUDED ITEMS

1 x PowerCon male cable connector (cod. 0520P014)
1 x XLR 5 Pins male cable connector (cod. 0508B028)
1 x XLR 5 Pins female cable connector (cod. 0508B027)
2 x Omega bracket (cod. 02K00549)

LED WASH PROJECTORS



PHOTOMETRIC DATA (EVEN BEAM COVERAGE)



	mt 5 ft 16.40	mt 10 ft 32.81	mt 15 ft 49.21	mt 20 ft 65.62	mt 25 ft 82.02	
Lux center	22000	5500	2444	1375	880	Beam angle 8°
Foot candles	2045	511	227	128	82	
Diameter cm.	70	140	210	280	350	
Diameter ft.	2.29	4.59	6.88	9.18	11.47	
Lux center	1537	384	171	96	61	Beam angle 52°
Foot candles	143	36	16	9	6	
Diameter cm.	488	975	1463	1951	2439	
Diameter ft.	16	32	48	64	80	

DMX CHANNELS

1 PAN msb	18 GREEN SECTOR 2
2 PAN lsb	19 BLUE SECTOR 2
3 TILT msb	20 WHITE SECTOR 2
4 TILT lsb	21 RED SECTOR 3
5 SPEED MOVEMENT	22 GREEN SECTOR 3
6 PAN FPR	23 BLUE SECTOR 3
7 SHUTTER	24 WHITE SECTOR 3
8 DIMMER	25 WHITE
9 RED CENTER	PREPROGRAMMED
10 GREEN CENTER	26 CTC
11 BLUE CENTER	27 MACROS
12 WHITE CENTER	28 MACROS SPEED
13 RED SECTOR 1	CONTROL
14 GREEN SECTOR 1	29 FUNCTIONS
15 BLUE SECTOR 1	30 ZOOM CENTRE /
16 WHITE SECTOR 1	GLOBAL ZOOM
17 RED SECTOR 2	31 ZOOM SECTORS
	32 ZOOM MODE
	33 SERVICE
	34 RESET